

USGS STM SENSOR RECOVERY FORM (one form per housing)

DATE: 9/1/12 STORM: BSAAC INSPECTORS: CAB/CKL

Housing # _____

SITE INFO

SITE ID: HWM-2A-STT-003 LAT (DD to 6 places): 30.26504
(format: SSS-ST-COU-###PP; see SOP)

SITE NAME: Intersection of Nunez Rd @ Hwy 433 LONG (DD to 6 places): 89.83965

STATE: CA COUNTY: S Tammany Landowner Info: Notified (Yes/No) Name: _____

SENSOR INFORMATION

Sensor Type (circle one):

Hobo Troll

RDG RDW

HWM

Other? _____

Serial # _____

Deployed as (circle one):

Water level (WL)

Baro Pressure (BP)

Wave Height (WV)

HWM

Other? _____

Data Interval:

30 sec 2 sec Other: _____

Sensor Deploy Time (GMT): _____

Data Start Time (GMT): _____

Sensor in Water (Y/N) _____

BP sensor collocated?

(Yes/No)

BP Site ID: _____

USGS VI on housing?

(Yes/No)

DETERMINE WATER SURFACE

Water Surface Reference Point (WSRP) Info

Reference Point (WSRP) # _____

WSRP elevation (feet): _____

Elevation Assumed? (Yes/No)

WSRP description:

Water Surface (WS) Elev. Calculations

TD Time: _____ GMT

WSRP elevation (WSRP): _____ feet


Tapedown (A): _____ feet

Weight length (B): _____ feet

Total TD (A + B): _____ feet

WS = WSRP - (A + B): _____ feet

WS conditions (circle)? Calm Choppy Wavy



DETERMINE THE SENSOR HOUSING ELEVATION

To determine the Sensor Housing Elevation using a tapeup/tapedown from the established water surface elevation above, use the box to the right.

Choose option!

If elevation run to 2nd RP (SHRP) above sensor, then use lower boxes.

Sensor Housing Nut Elevation (D) from WS


Water Surface (WS): _____ feet

Nut in water? Tape up to nut _____ feet

OR

Nut out of water? Tape down: _____ feet

D = (WS +/- C) - S: _____ feet



Sensor Housing RP Info

Reference Point (SHRP) # _____

SHRP elevation (feet): _____

Elevation Assumed? (Yes/No)

RP description:

Sensor Housing Nut Elevation (D) from SHRP

SHRP elevation: _____ feet


Tapedown (A): _____ feet

Weight length (B): _____ feet

Total TD (A + B): _____ feet

Subtract slippage (S): _____ feet

D = SHRP - (A + B) - S: _____ feet



Flip over to Page 2

4.22

GPS 2.705
2.611

2.658 + 4.22 = 6.878

HWM elev.

Tape down from point on concrete for elevation

USGS STM SENSOR RECOVERY FORM (page 2)

SENSOR ORIFICE ELEVATION	Sensor Orifice Elevation ($G = D - E$) Housing Nut (D): _____ feet Subtract Housing Correction Factor (E): _____ feet <div style="border: 1px solid black; padding: 5px; display: inline-block;"> Sensor Orifice Elevation (G): _____ feet </div>		SENSOR HEIGHT ABOVE GROUND	Use if Sensor Deployed Above Ground w/ no RP Elevation ($OEG = D - (H - E)$) Housing Nut (D): _____ feet TD to Ground (H): _____ feet Subtract Housing Correction Factor (E): _____ feet Data offset for Depth above Ground (OEG): _____ feet <i>This is used only until RP elevation is surveyed in to get initial estimate of depth above ground surface</i>	

DRAW SITE SKETCH BELOW

Excellent mud line on outside wall of Auto Body shop.
CRB Automotive.

**CHECK
IN!!**

Pictures Taken (circle all that apply): Sensor RP RM North South East West
 Departure Time: _____ GMT Check-In Time: _____ GMT STM Coord. on duty: _____